

# Atto POS 1000



Projective  
Capacitive Touch



15" Second Display



Magnetic Card Reader



VESA Mount Capable



**SEVOR**

Quality. Safety. Versatility



**Technical Specifications\*:**

<b>Size</b>	15" TFT LED
<b>Resolution</b>	1024 x 768
<b>Brightness</b>	400cd/m <sup>2</sup>
<b>Colour</b>	16.7 M
<b>Contrast Ratio</b>	600:1
<b>Touch system</b>	Multi point projective capacitive touch screen
<b>Host board</b>	MINI-ITX MP1900
<b>CPU</b>	Intel® Quad-Core Celeron® J1900 (2.0GHz)
<b>RAM</b>	4GB DDR3 RAM
<b>Chipset</b>	Intel® Vallerview SSA-CUNIT
<b>Storage</b>	M-SATA SSD 64G
<b>LAN</b>	1×Gigabit LAN 10/100/1000 Mbit
<b>Audio</b>	Realtek ALC887@ VALLERVIEW High Definition Audio Controller
<b>I/O Ports</b>	Without Base: 3xUSB 2.0, 1xUSB 3.0, <b>1x RS232</b> , 1xVGA, 1xAudio out, 1xLPT, x1 Ethernet port With base: 3xUSB 2.0, 1xUSB 3.0, <b>3x RS232</b> , 1xVGA, 1xAudio out, 1xLPT, x1 Ethernet port, <b>1xPS2(KB/MS), 1x12V output</b>
<b>Expansion bus</b>	1×PCI Express×1 1×Mini PCIE
<b>Operating System</b>	Windows POSReady 7 / Windows 7 Pro / 10 IoT / 10 Pro
<b>Operating temperature</b>	0° to 40° C
<b>Storage temperature</b>	-10° to 60° C
<b>Relative Humidity</b>	20% to 80% non-condensing
<b>Power input</b>	100-240VAC ~ 50-60HZ 1.5A
<b>Power output</b>	12VDC 4A MAX
<b>Material structure</b>	Aluminium Die Cast
<b>Installation</b>	Desktop / VESA
<b>Weight</b>	5.65 kg
<b>Dimension</b>	Without base: 350(W) x 292 (H) x 46 (D)mm ; With base: 350(W) x 282 (H) x 149 (D)mm

\*Technical specifications are subject to change without notice based on availability.



Multi Point Projective Capacitive Touch Screen



VESA Mount Capable



15" Second Display



Die Cast Casing



Fanless Design

**The Senor Building**

65 & 67 Weaver Street  
Coopers Plains QLD 4108  
Brisbane, Australia

[www.senortech.com.au](http://www.senortech.com.au)

P: +61 7 3275 5888  
F: +61 7 3275 5800  
sales@senortech.com.au

